

SPECIFICATION:

ENGINE

Kubota D1803M
39.5 Gross SAE hp @ 2700 rpm
31.0 PTO hp @ 2700 rpm
3 cyl., 1826cc

TRANSMISSION

Hydrostatic (HST) 3 Ranges
Foot pedal control of speed and
direction changes
Cruise Control

STEERING

Hydrostatic Power Steering
Bi Speed with Electronic Control

TRAVEL SPEEDS

0 to 30.0-kph forward
0 to 21.7-kph reverse

HYDRAULICS

37.6 litres/min. total
23 litres/min. for Loader
1,150 Kg Lift cap. @ Link Ends
Position Control Std
2 x D/A (1 x changeable to S/A) and
1 x S/A Remote Std

PTO

Electro Hyd Engagement
Rear PTO 540/800 rpm
Mid PTO 2500 rpm
Independent & Simultaneous
Operation of Mid and Rear PTO
possible
Live Drive

DIFF LOCK

On Rear Axle

BRAKES

Wet Disc Type

STANDARD EQUIPMENT:

Folding ROPS (not per brochure), Power Steering with Electronic Bi-Speed Turn, Key Stop, Flat Deck with Rubber Mat, Tilt Steering, Seat, Headlights with High and Low Beam, 2 Tail Lights, Stop Lights, Indicators, Under Bonnet Muffler, Cruise Control, Temperature Gauge, Fuel Gauge, Tachometer, Hour Meter, PTO Light, Handbrake Warning Light, Front Tow Hitch, 2 x D/A Remotes and 1 x S/A Remote.

OPTIONAL EQUIPMENT:

Weights: Frame and 4 x 20 Kg Weights
Mid Mower: RCK60-35ST 60" Side Discharge Mower and Hydraulic Lift Kit.
Loader: We recommend the Kubota LA40 ST-1 Loader.
Industrial Tyres: TRS will trade STD Turf Tyres & supply industrials to fit STD Turf Rims
TRS can supply industrial tyres & rims to replace 6-12 ags (no trades)



TYRES

Front Ag 6x12
Rear Ag 12.4x16
Front Turf 24x8.50-14
Rear Turf 13.6x16

Optional:

Industrial tyres in lieu of Turfs
(ex TRS)

DIMENSIONS

Weight 975 Kg
Length 2650 mm
Length with 3pl 2800 mm
Width Ag Rear 1465 mm
Width Ag Front 1220 mm
Width Turf Rear 1410 mm
Width Turf Front 1260 mm

Height Top S/Wheel 1430 mm
Height Top Seat 1420 mm
Height Top ROPS 2226 mm

LA402 ST-1

Joystick standard 1370 mm
Bucket width (54")
Bucket cap. Level 0.19 m³
Bucket cap. Heaped 0.23 m³
Lift cap. @ bucket pin 480 kg
Lift cap. @ bucket centre 345 kg
Nett weight approx. 359 kg

